


168282 - MTC 54.200 ER STAALDRAADGOOT +KOPP. L=3



Product data

Product code:	168282
Brand:	Niedax Group
Series:	Niedax Wired mesh
Type:	MTC
EAN Code:	03614987131106
Technical description:	MTC 54.200 ER STAALDRAADGOOT +KOPP. L=3
ETIM class:	EC000853 - Mesh cable tray

Technical data

Colour:	Other
Width:	200
Model:	Integrated connector
Height:	54
Type of connection:	Click in mounting
RAL-number:	-
Surface protection:	Other
Weight:	1.04825
Material quality:	Stainless steel 304 (1.4301)
Length:	3000
Working temperature:	-20 - 120
Material:	Stainless steel
Integrated partition:	None
Usable cross section:	10220
Profile shape:	U-shape
Working length:	3000

Suitable for circuit integrity:	No
Load test type according to IEC 61537:	Type III
Diameter longitudinal wire:	3.9
Diameter transverse wire:	3.9
Possible support spacing:	- - -
Safe working load according to IEC 61537 with support spacing 0.5 m:	-
Safe working load according to IEC 61537 with support spacing 1.0 m:	-
Safe working load according to IEC 61537 with support spacing 1.5 m:	300
Safe working load according to IEC 61537 with support spacing 2.0 m:	200
Safe working load according to IEC 61537 with support spacing 2.5 m:	150
Safe working load according to IEC 61537 with support spacing 3.0 m:	-
Safe working load according to IEC 61537 with support spacing 4.0 m:	-
Safe working load according to IEC 61537 with support spacing 5.0 m:	-
Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 7.0 m:	-
Safe working load according to IEC 61537 with support spacing 8.0 m:	-
Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Safe working load according to IEC 61537 with support spacing 9.0 m:	-
Safe working load according to IEC 61537 with support spacing 11.0 m:	-
Safe working load according to IEC 61537 with support spacing 12.0 m:	-